TX7156 – Mobile Projector

Ultra Bright, Light Weight Multimedia Solution

At only 3.2 pounds, the TX7156 from Optoma unleashes 3000 ANSI lumens of brightness, breaking the portability/brightness barrier. Whether traveling across the country or down the hall, the TX7156 provides images that will capture your audience's attention.

Features

- Ultra-portable 3.2-pound DLP® projector
- Bright enough for even large conference rooms – 3000 ANSI lumens
- Easy-to-read text - native XGA resolution, 2500:1 contrast ratio (full on/full off)
- Ideal presentation remote with mouse control and laser pointer
- Rapid power-on and shutdown – saving you time and money
- Filter-free design means low cost of ownership
- Built-in closed captioning

Specifications

Display Type
Single 0.55" DMD DLP Technology by Texas Instruments

Resolution
Native XGA (1024 x 768)

Maximum Resolution
UXGA (1600 x 1200)

Brightness (Typical)
3000 ANSI Lumens

Contrast Ratio
2500:1 (Full On/Full Off)

Lamp Life and Type
3000/2000 Hours (STD/Bright)
220W SHP

Throw Ratio
1.8 to 2.2:1 (Distance/Width)

Projection Distance
3.9' to 39.4' (1.2 to 12m)

Image Size (Diagonal)
26.87" to 311.1" (0.68 to 7.9m)

Aspect Ratio
4:3 Native, 16:9 and 16:10 Compatible

Remote Control
Fully Featured IR Remote with Laser Pointer and Mouse

Audio
One 1-Watt Speaker

Displayable Colors
134 Million

Offset
114%

Computer Compatibility
UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, VESA, PC and Macintosh Compatible

Video Compatibility
NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

Projection Lens
F= 2.55-2.72, f= 21.3-24.5 mm, 1.15x Manual Zoom and Focus

User Controls
Complete On-Screen Menu Adjustments in 22 Languages

I/O Connectors
HDMI v1.3, VGA-In, Composite Video, S-Video, Audio-In and USB

Security
Kensington Lock Port

Projection Method
Front, Rear, Ceiling Mount, Table Top

Weight
3.2 lbs (1.4kg)

Dimensions (W x H x D)
8.66" x 2.79" x 7.0"
(220 x 71 x 178 mm)

Noise Level (STD/Bright)
33dB/36dB

Horizontal Scan Rate
15, 30 - 91.4 KHz

Vertical Refresh Rate
43 - 87 Hz

Keystone Correction
± 30° Vertical

Uniformity
85%

Operating Temperature
41 to 104°F (5 to 40°C), 80% Max Humidity

Power Supply
AC Input 100-240V, 50-60Hz, Auto-Switching

Power Consumption
280 Watts (Bright), 230 Watts (STD), <5 Watts (Standby)

Standard Accessories
AC Power Cord, VGA to VGA Cable, USB Cable, Remote Control, Batteries for Remote, Lens Cap, Carrying Case, CD-ROM User's Manual, Quick Start Card and Warranty Card

Optional Accessories
Ceiling Mount, VGA to Component Cable, S-Video Cable, HDMI Cable, Composite Video Cable, Panoview™ Series Screens

Warranty
Three Years Optoma Express Replacement Service, One Year on Lamp

UPC
796435 41 109 1

Accessory Part Numbers
Lamp: BL-FS220B
Remote: BR-5028L
Mount: BM-5001U
Case: BK-4021

© Copyright 2009 Optoma Technology, Inc. All specifications subject to change at any time. DLP® and the DLP logo are registered trademarks of Texas Instruments.